## **Perform Series, Torso Rotation**

The Perform Series Torso Rotation is designed to isolate and work internal and external oblique muscles through a smooth multi-directional rotation movement. The unique ratcheting system allows users to easily adjust the starting position to their individual preference, whilst the chest, thigh and seat pads maximise oblique engagement and limit lower back stress.





Water Bottle Holder

Instuctions placard





High-density Poly-foam

Adjustable Seat



## **Technical Specifications**

| Rating                 | Commercial   |  |
|------------------------|--|--|
| Adjustments            | Adjustable seat for user comfort and to allow easy operation   |  |
| Upholstery             | High-density poly-foam and double stitches offer comfort and endurability  |  |
| Tubing                 | Tube of the functional part is primarily at a 3mm thickness. The weight stack cage is with D-shape tube size: 95 x 81.1 x 3mm and a racetrack tube size: 50 x 100 x 3mm which ensure ultra-durability and stability. |  |
| Instructions<br>Plaque | Instructions placards to review proper set-up, movement and muscles trained  |  |
| Shroud                 | Translucent ABS shroud at a thickness of 3.2mm ensures ultra-durability and shock resistance.  |  |
| Weight Stack           | 72.5kg<br>160lbs   |  |
| Product Weight         | 127.3kg<br>280.6lbs  |  |
| Maximum User<br>Weight | 150kg<br>330lbs  |  |
| Dimensions             | L 122.1 x W 120.2 x H 150.6 cm<br>L 48 x W 47.3 x H 59.2 inches  |  |

## **Key Features**

| Space efficient design requires minimal floor space   | • |
|---|---|
| Self-lubricate American loos™ cable with nylon-coated 12 complex fiber ensures service life more than 250 thousand times. | • |
| Water bottle holder fixed on the cage is within reach.  | • |
| Ergonomic handlebars in TPV material with aluminium ring limit offers comfort and security during a workout               | • |
| All dynamic components are shielded for safety purpose  | • |
| Lathed pulley with bearings of less tolerance ensure smooth movement  | • |
| Meets EN957 safety regulation   | • |



