



## 30mm Premium Rubber Tile

The 30mm Premium Rubber Gym Tile has a hard-wearing ultra-fine granule surface layer and a medium granule base layer. The Premium tiles are more abrasive resistant than standard rubber tiles.



Ramp Edges Available



Corner Tiles Available



### Technical Specifications

<b>Tile Size</b>	1m x 0.5m x 30mm (2 tiles = 1 Square Metre)
<b>Tile Colour</b>	Black with a 15% EPDM White/Grey colour Fleck
<b>Tile Material</b>	100% Recycled Rubber, NR SBR – Natural Rubber / Styrene-butadiene Rubber
<b>Base layer</b>	2-3mm granules
<b>Surface Layer</b>	3mm thickness for extra strength & protection, fine-grained recycled tyre rubber (black) and 15% of coloured EPDM granules bonded with Polyurethane elastomer.
<b>Floor Hardness</b>	is 60+/-5 ShA
<b>Sound Insulation</b>	28dB (ISO 10140-3)
<b>Simple Installation</b>	No floor adhesive required, tiles connect together with hidden dowels underneath on all sides to prevent any movement.
<b>Resistance to chemicals</b>	good resistance to acids, alkalis and salts. Contact with oils and hydrocarbons is not advisable and will damage the floor tiles.
<b>Tools Required for Fitting</b>	Stanley knife and Rubber hammer
<b>Cleaning</b>	Vacuum on general setting, then lightly mop with a micro fibre mop and water mixed with a ph neutral cleaner. Do not flood the floor with water.

### Key Features

<b>Easy Cleaning and bacteria-resistant</b>	•
<b>Withstand the impact of intense workouts &amp; dropped weights easily and tirelessly</b>	•
<b>Improves traction, offers excellent shock absorption and allows for quicker acceleration</b>	•
<b>Absorption of noise</b>	•
<b>Loose lay with the plastic block connector provided</b>	•
<b>100% Recycled Rubber</b>	•
<b>Also available in 20mm &amp; 40mm</b>	•